

BeVision D2

A Precise Vision of Particles



BeVision D2A Precise Vision of Particles



"The BeVision D2 is easy to use and quickly provides high-resolution results that are key to the quality assurance of our product line."

-- PetroChina Company Limited Petrochemical Research Institute

The BeVision D2 provides an efficient solution to the size and shape analysis of dry, high-flowability powders or granules. Tens of thousands of particles can be measured by a BeVision D2 within three minutes.

Combining a high-speed camera with a precise telecentric lens, the BeVision D2 is able to efficiently analyze the size and shape of particles in the range of $30 - 10,000 \mu m$.

The BeVision software helps you evaluate particle size and shape from 24 different aspects and further organizes the data into an all-around validation of particles.

Measuring 10, 000 particles within

3 minutes*

*Sample and sample preparation dependent

high-speed camera

captures free-falling particles

Real-time

results during measurements

Features and Benefits

- Measurement range: 30 10,000 μm
- 24 different particle size and shape parameters
- · Reduction of workload and time
- Outstanding reproducibility
- Fully automated operation
- Results in compliance with ISO 9276-6
- Powerful software provides a comprehensive evaluation
- Comparable with sieving results

Why **Image Analysis** Method?

Why **Dynamic Image Analysis** Method?

Easy

Capture an image of particles, identify particles, then measure their size and shape. Every step of image analysis is easy and clear.

Shape analysis

Based on a direct view of particles, it is possible to analyze not only the size of particles, but also their shape.

Seeing is believing

The image analysis method determines the size and shape of every individual particle and then sums it up to form a statistic.

Details of particle size or shape distribution can be accurately provided.



Efficiency

A continuous particle flow passing through the measurement zone helps achieve a higher efficiency of the measurement.

Oversized particle sensitivity

The dynamic image analysis method is sensitive to oversized particles; it is even possible to estimate the size of oversized particles.

Reliable results

The maximized number of measured particles ensures the statistical significance of measurement results.

BeVision Series: Precision in Particle Vision



BeVision S1

Classical and versatile static image analyzer for wet and dry measurements.



BeVision M1

Automated static image analyzer for wet and dry measurements.



BeVision D2

Dynamic image analyzer for dry measurement.

	Static Image Analysis		Dynamic Image Analysis
	BeVision S1	BeVision M1	BeVision D2
Measurement range	1 - 3,000 μm	1 - 10,000 μm	30 - 10,000 μm
Particle shape analysis	•••	•••	•••
High-resolution for narrow distributions	•••	•••	•••
Accuracy for broad distributions	•	••	•••
Reproducibility	•	••	•••
Small sample volume for a single analysis	•••	••	•
Undersized particles detection	•••	••	•
Oversized particles detection	•	•	•••
Simple operation and measurement efficiency	••	•••	•••
Individual particle analysis	•••	•••	••

© Bettersize Instruments Ltd.

BeVision D2 Hardware:

Guaranteed Accuracy and Efficiency for You


To measure the size and shape of particles over a great variety of applications, the BeVision D2 has equipped with a comprehensive range of hardware. Corresponding to the sample material properties, selecting the best hardware can help measure the size and shape of particles with optimum accuracy and efficiency.

Feeding chutes and funnels



To help particles flow appropriately during the test process, the BeVision D2 prepares several customization options for feeding chutes and the feeding funnel.

The customizable coating material for the funnel and chute can effectively prevent particles from sticking to the wall. The funnel size and the chute size are also customizable based on requirements, permitting the BeVision D2 to hold an appropriate volume of samples.



Adjustable feeding guides



The feeding guide is used to orient the particle flow in the focusing range of the objective lens, thus the quality of captured images and accuracy of measurements are ensured.


Based on the approximate particle size, the width of feeding guide openings can be adjusted to achieve a balance between the feeding rate and the quality of images.

Objective lens



Depending on the approximate particle size and the width of the particle size distribution, the BeVision D2 offers 5 optional objective lenses to ensure measurement accuracy.

Each optical lens has its own efficient working range, to accurately measure particle size and shape of a great variety of samples. According to ISO 13322, it is recommended to select a working range covering the whole size distribution range of the sample.



able to detect particles, rough size measurement

size and rough shape measurement


size and shape measurement in ISO-area

BeVision Software: Visualized Insights for You

Distribution curves and charts present particle size and shape distributions, and the scattering plot shows the relationship between two different particle size and shape parameters. All these charts, curves, and tables are customizable.

Distribution in summary

The BeVision software offers statistics and typical values to describe particle size and shape distributions, e.g., the D[1,0], span value, D90. The typical value chart is customizable.



For irregularly shaped particles, it is hard to describe their size with a single dimension. Scanning over 180 different directions of each particle projection, the BeVision software is able to precisely analyze particles, and present the particle size and shape in 24 different parameters. The size and shape parameters are in compliance with ISO 9276-6.

→ Locate particles

The BeVision software offers a single particle gallery that can be the direct way to locate particles with a specific appearance. Besides, the BeVision software allows users to find particles with specific characteristics, with a customizable filter.


Reproducible measurements

To ensure a reproducible result, the BeVision software can make a measurement automatically, following a saved standard operation procedure (SOP).




Comparable results

The record comparison function makes it possible to do a comparison among multiple records: particle size or shape distribution comparison, typical value comparison, etc.



Reports keep flexible

The BeVision series prepares various report templates for different use. Layouts and contents of report templates are editable and customizable.



Particle Size and Shape **Parameters**

Size parameters

Equivalent diameters:

area-equivalent diameter perimeter-equivalent diameter

Feret diameters:

maximum and minimum Feret diameters, x_{LF} ("length")

Martin diameters:

maximum and minimum Martin diameters

Legendre ellipse:


major and minor axes




A: projected area of the particle




P: length of the projected contour




 x_{B1} , x_{B2} : long and short diameters





xn: perimeter- equivalent diameter




x₄: area- equivalent diameter









Shape parameters

Size difference in 2 directions:

aspect ratio L/W ratio ellipse ratio

Round-likeness and rectangle-likeness:

circularity irregularity compactness extent box ratio

Contour concavity:


concavity convexity solidity

For elongated particles:

elongation straightness

$Aspect\ ratio = \frac{x_{Fmin}}{}$








 $Compactness = \frac{x_A}{}$


$$Extent = \frac{A}{x_{Fmax} \times x_{Fmin}}$$

$$Concavity = \frac{A_C - A}{A_C}$$

$$Solidity = \frac{A}{A_C}$$




 $Circularity = \frac{x_A}{}$






Elongation = $\frac{1}{L_s}$



 $Irregularity = \frac{D_{imax}}{D_{imax}}$



Convexity = $\frac{P_C}{P_C}$



 $Straightness = \frac{x_{Fmax}}{L_G}$

Typical Applications

Agriculture

Food and Beverages




Mining and Minerals





Additive Manufacturing




Plastic and Resins



Application Cases

Natural sands

Researchers of a variety of industries, e.g., the oil and gas industry, place great importance on the morphological information of soils and sediments. The natural sands challenge image analyzers from 2 aspects: the size and shape of natural sands are distributed in a wide range and the efficiency of the shaping process. The BeVision D2 gets over these challenges with its wide measuring range and excellent efficiency and helps a research team of the China University of Petroleum successfully measure the size and shape of natural beach sand samples.




Sandstone sample particle morphology

Adapted from Yan, Y., Zhang, L., Luo, X., Li, C., Hu, F., A new method for calculating the primary porosity of unconsolidated sands based on packing texture: Application to modern beach sand, Mar. Pet. Geol., 2018, (98), 384-396.

Grains

The size and shape of cereal particles, especially refined grains, affect the quality and value of the final product. To help monitor the size and shape of cereals, the BeVision D2 offers high-resolution measurement results at good efficiency. The scatter plot showing the relationship between particle size (xA) and aspect ratio, helps QC engineers handle the size-shape distribution of the rice kernel sample and measure the content of broken rice and impurities.



© Bettersize Instruments Ltd. © Bettersize Instruments Ltd.

General		
Measuring principle	Dynamic image analysis method	
Parameters	Particle size, shape, and number	
Measurement performance		
Measuring range	30 – 10,000 μm	
Typical measurement time	1 to 3 min *	
Number of size / shape classes	100 (user adjustable)	
Special functions	SOP settings, automatic tests, analysis of saved images	
Main device		
High-speed CCD camera	Up to 120 images per second	
Light source	White LED stroboscopic parallel light source	
System parameters		
Dimensions (L × W × H)	61.0 × 35.0 × 44.0 cm	
Weight	26 kg	
Supply voltage	100 / 240 V, 50 / 60 Hz	
Software		
Conformity	ISO 13322, ISO 9276	
Reports	Customizable reporting	

^{*} Sample and sample preparation dependent



Bettersize Instruments Ltd.

Website: https://www.bettersizeinstruments.com

Email: info@bettersize.com

Address: No. 9, Ganquan Road, Jinquan Industrial Park,

Dandong, Liaoning, China

Postcode: 118009

Tel: +86-415-6163800 Fax: +86-415-6170645 Visit Our BeVision D2 Site:



Visit Our Official YouTube Channel:



Disclaimer. By using or accessing the brochure, you agree with the Disclaimer without any qualification or limitation. Diligent care has been used to ensure that the information in this brochure is accurate, Bettenize instruments Ltd. shall not be liable for errors contained herein or for damages in connection with the use of this material. The information on this brochure is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or control. Retterzier Instruments Ltd. reserves the right to modify, alter, add and delete the content outlined in the brochure without prior notice and without any subsequent liability to the company.

Copyright: © 2022 Bettersize Instruments Ltd. | All Rights Reserved