THE HIGH-PRESSURE HOMOGENIZERS



/ CELL-DISRUPTION / DEAGGLOMERATION / DISPERSIONS
 / EMULSIONS / LIPOSOMES / PARTICLE SIZE REDUCTION
 / POLYMER MW REDUCTION / STABILIZATION / ...AND MORE

1010





PSI-30

- up to 2068 bar
- / up to 50Hz 40 L/h 60Hz 46 L/h
- / less than 67 dBA
- / small footprint

Its compact size and quiet operation do not compromise its capabilities in terms of maximum pressure and flow rate. The **PSI-30** is just great for lab work, with batches as small as 100 ml, but is also an excellent smallscale production workhorse, even in continuous process configurations, with a dead volume of 15ml.

FOOTPRINT W×L×H 650×900×1126 mm

POWER

3×380V 50Hz, 3×400V 50Hz 3×220V 60Hz, 3×480V 60Hz

WEIGHT 162 kg

 FLOWRATE

 50Hz
 40 L/h
 60Hz
 46 L/h

MAX PRESSURE 2068 bar The choice of the best materials and finishing make the PSI-30 suitable for every industry, including the most demanding pharmaceutical, biochemical and food processing environments.

Every unit comes with a comprehensive standard equipment, including an electropolished shell-tube heat exchanger, an easy to use user interface and built-in data acquisition capabilities, but there are many accessories and options to make the PSI-30 the perfect fit for your needs, like GMP compliant record handling, remote control, NIST traceable temperature and pressure sensors.

RIFERIMENTO PER L'ITALIA



Qi srl t +39 06 9105461 www.qitech.it | SalesQi@qitech.it



CONTACT US info@psi-instruments.com www.psi-instruments.com

WORK SMARTER